ADDID[®] 240

Special features

- increases conductivity very effectively
 solvent-free
- highly suitable for clears

Examples of application

2-pack coatings based on epoxies and polyurethanes

recommended addition level As supplied calculated on total formulation: 1.0 - 8.0 %

Solubility

1 : 100	1:4
+	+
+	+
-	-
-	-
-	-
-	-
-	-
-	-

+ = clear, soluble, o = opalescent, - = cloudy, insoluble

Processing instructions

- Addition as supplied is recommended.
- Addition to the grind is recommended in pigmented formulations.
- Incorporate the product in 2-pack formulations based on epoxy preferably into the amine component.
- Incorporate the product in 2-pack formulations based on polyurethane preferably into the polyol component.

Chemical description

quaternary nitrogen-compound

Technical information

 delivery form 	liquid
- appearance	yellowish liquid
- active matter content	100 %
 viscosity at 25 °C 	approx. 2500 mPa s

Registration status

ADDID[®] 240 respectively its ingredients are listed in the following chemical inventories: DSL, EINECS, TSCA, TCSI.

All intentional ingredients are listed on the DSL (Domestic Substance List) inventory or have been notified pursuant to the NSN (New Substances Notification) regulations.

All intentional ingredients are listed on the TSCA inventory or comply with the TSCA Polymer Exemption criteria according 40 CFR 723.

Packaging

plastic pail 25 kg

Storage stability

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

Solidification may occur at temperatures below 10 $^{\circ}\text{C},$ product becomes liquid again after warming. Product properties are not affected by this process.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade (Status: 11/2015)

Evonik Resource Efficiency GmbH · Goldschmidtstrasse 100 · 45127 Essen · Germany · PHONE +49 201 173-2222 · FAX +49 201 173-1939 · www.tego.de

antistatic additive