

SILIKOPON® EC

silicone epoxy resin

Special features

- excellent adhesion, chemical and solvent resistance
- heat stable
- excellent corrosion resistance

Technical information

appearance	clear to hazy liquid
non-volatile content	approx. 52 %
solvent	methoxypropylacetate
viscosity at 25 °C	approx. 1000 mPa s
epoxy equivalent weight calculated on non-volatile content	approx. 1960 g

Suitability for

solventborne	pigmented
●	●
direct grind	2-pack coatings
●	○

● = suitable ... ○ = not suitable

Application

- high-temperature anti-corrosion
- anti-corrosion coatings (depending on formulation)
- muffler coatings for vehicles, in particular motor bikes

Processing instructions

- Because of the strong yellowing, only the formulation of dark colors is recommended.
- Limited miscibility with aromatic hydrocarbons.
- Use with metallic pigments and special formulations to obtain continuous heat-resistance of up to 650 °C.
- Application by spray (incl. electrostatic), dipping or brushing.

Dilution

Dilutable by esters, ketones and glycol ethers.

Baking conditions

250 °C/30 min

Registration status

SILIKOPON® EC respectively its ingredients are listed in the following chemical inventories: ECL, EINECS, NDSL, PICCS, TSCA, TCSI.

All intentional ingredients are listed on the TSCA inventory or comply with the TSCA Polymer Exemption criteria according 40 CFR 723.

Further information on regulatory topics can be found on the Regulatory Data Sheet.

All intentional ingredients are listed on the ECL inventory or comply with the Polymer Exemption criteria.

All intentional ingredients are listed on the PICCS inventory or comply with the Polymer Exemption criteria.

Packaging

steel drum 200 kg

Storage stability

When stored in an original unopened packaging between -10 and +40 °C, the product has a shelf life of at least 12 months from the date of manufacture.

However, contact with tin (e.g. with metal containers) will shorten storage stability.

Keep dry. Contact with moisture causes gelation.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.
(Status: 11/2015)

Evonik Resource Efficiency GmbH · Goldschmidtstrasse 100 · 45127 Essen · Germany · PHONE +49 201 173-2222 · FAX +49 201 173-1939 · www.tego.de