
TEGO[®] Foamex 3062

defoamer concentrate

Application recommendations



0 = unsuitable...5 = highly suitable

Special features

Very strong defoaming and foam-destruction effect in millbases and high-viscosity formulations.

Suitability for

waterborne	solventborne
•	D
2-pack 100 %	radiation-curing
0	0
clear coat	pigmented
D	

● = suitable ... () = not suitable

Addition to

grinding stage	let-down stage	
•	0	

● = suitable ... ○ = not suitable

Solubility in

water	ethanol
0	D
TPGDA	butyl acetate
•	D
white spirit	
•	

• = clear soluble, \bullet = cloudy but stable, \bigcirc = insoluble

Recommended addition level

As supplied calculated on total formulation: 0.05 - 0.5 %

Processing instructions

- Particularly suitable for addition to the grind.

- Addition during the let-down or in clears requires high shear conditions or predilution.
- The long-term effectiveness of the defoamer is dependent on the formulation and should be tested in the individual formulation
- (different temperatures are suggested).

Formulation advices

Alternatives with better compatibility: TEGO° Foamex 883, TEGO° Airex 901 W

Chemical description

polyether siloxane copolymer, contains fumed silica

Technical information

- active matter content

- appearance

- slightly hazy liquid
- 100 %

Suitability for food contact

- The additives/monomers/solvents of TEGO® Foamex 3062 are listed on the A and B lists of the Swiss Ordinance 817.023.21, Annex 6.
- Detailed information on the BfR- and 10/2011 status is available on request.

Registration status

TEGO[®] Foamex 3062 respectively its ingredients are listed in the following chemical inventories: AICS, DSL, ECL, EINECS, ENCS, IECSC, PICCS, TSCA, NZIOC, TCSI.

All intentional ingredients are listed on the DSL (Domestic Substance List) inventory or have been notified pursuant to the NSN (New Substances Notification) regulations.

All intentional ingredients are listed on the TSCA inventory or comply with the TSCA Polymer Exemption criteria according 40 CFR 723.

Further information on regulatory topics can be found on the Regulatory Data Sheet.

All intentional ingredients are listed on the ECL inventory or comply with the Polymer Exemption criteria.

All intentional ingredients are listed on the PICCS inventory or comply with the Polymer Exemption criteria.

Packaging

plastic pail 25 kg plastic L-ring drum 200 kg

Storage stability

When stored in an original unopened packaging between -40 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used. (Status: 11/2015)

Evonik Resource Efficiency GmbH · Goldschmidtstrasse 100 · 45127 Essen · Germany · PHONE +49 201 173-2222 · FAX +49 201 173-1939 · www.tego.de