

Evonik Corporation EP 2325 Adhesion Resin

Category : Polymer , Thermoset , Polyester, TS

Material Notes:

A special purpose, medium hard polyester resin with a wide solubility and compatibility designed as a supplementary resin to improve the adhesion of numerous coating systems even on critical substrates

Order this product through the following link:

http://www.lookpolymers.com/polymer_Evonik-Corporation-EP-2325-Adhesion-Resin.php

Physical Properties	Metric	English	Comments
Density	1.05 g/cc	0.0379 lb/in ³	DIN 51 757
	@Temperature 23.0 °C	@Temperature 73.4 °F	
	1.24 g/cc	0.0448 lb/in ³	DIN 53 479-B
	@Temperature 23.0 °C	@Temperature 73.4 °F	
Viscosity	500 cP	500 cP	DIN EN ISO 3219
	@Temperature 23.0 °C	@Temperature 73.4 °F	

Thermal Properties	Metric	English	Comments
Softening Point	60.0 °C	140 °F	DIN 53 181
Glass Transition Temp, Tg	30.0 °C	86.0 °F	DIN 53 765

Optical Properties	Metric	English	Comments
Gardner Color Number	2.0	2.0	DIN ISO 4630

Chemical Properties	Metric	English	Comments
Total Acid Number	18	18	[mg KOH/g]; DIN EN ISO 2114

Descriptive Properties	Value	Comments
Hydroxyl Number (mg KOH/g)	16	DIN EN ISO 4629
Nonvolatile matter (%)	60	DIN EN ISO 3251

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China