

Product information

AEROSIL® R 976 S

Hydrophobic fumed silica

Characteristic physico-chemical data

Properties and test methods	Unit	Value
Specific surface area (BET)	m²/g	215 - 265
pH value in 4% dispersion		4.0 - 5.5
Loss on drying 2 hours at 105 °C	%	≤ 0.5
C content	%	2.0 - 2.6
Bulk density*	g/l	арргох. 50
SiO ₂ content based on ignited material	%	≥ 99.8
ata III.		

* ex plant

The data represents typical values (no product specification)

Registrations (substance or product components)

AEROSIL® R 976 S

CAS-No.	68 611-44-9	
EINECS (Europe)	registered	
TSCA (USA)	registered	
DSL (Canada)	registered	
AICS (Australia)	registered	
ENCS (Japan)	registered	
KECI (Korea)	registered	
IECS (China)	registered	
PICCS (Philippines)	registered	

AEROSIL* R 976 S is a hydrophobic fumed silica aftertreated with DDS (Dimethyldichlorosilane).

Applications and properties

Applications

- Silicone rubber and silicone sealants
- Paints and coatings
- Printing inks and toner
- Adhesives
- Cable compounds and gels
- Plant protection

Properties

- Hydrophobic component for thickening and reinforcement of silicone rubber
- Improves shelf-life of silicone sealants
- Water resistant, hydrophobising of liquid systems
- Rheology control of (complex) liquid systems
- For use in coatings as anti-settling agent, for pigment stabilization and improvement of corrosion protection
- Improves hydrophobicity and rheology of offset printing inks
- Improvement and maintenance of free flow and anti-caking characteristics of powders

Safety and handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Evonik Resource Efficiency GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com or can be downloaded from our homepage www.aerosil.com. We recommend to read carefully the safety data sheet prior to the use of our product.

Packaging and storage

AEROSIL® R 976 S is supplied in multiple layer 10 kg bags. We recommend to store the product in closed containers under dry conditions and to protect the material from volatile substances. AEROSIL® R 976 S should be used within 2 years after production.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Customer Service

Europe/ Middle-East/ Africa/ Latin America Evonik Resource Efficiency GmbH

Business Line Silica PB 010-A410 Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59 12532 FAX +49 6181 59 712532 aerosil@evonik.com

North America Evonik Corporation

Business Line Silica 299 Jefferson Road Parsippany, NJ 07054-0677 USA PHONE +1 800-233-8052 FAX +1 973-929-8502 aerosil@evonik.com

Asia (excluding Japan) Evonik (SEA) Pte. Ltd.

Business Line Silica
3 International Business Park
Nordic European Centre, #07-18
Singapore 609927
PHONE +65 6809-6877
FAX +65 6809-6677
aerosil@evonik.com

Japan NIPPON AEROSIL CO., LTD.

Marketing & Sales Division P.O. Box 7015 Shinjuku Monolith 13F 3-1, Nishi-Shinjuku 2-chrome Shinjuku-ku, Tokyo 163-0913 Japan PHONE +81 3 3342-1789 FAX +81 3 3342-1761 infonac@evonik.com www.aerosil.jp

Technical Service

www.aerosil.com

Europe/ Middle-East/ Africa/ Latin America Evonik Resource Efficiency GmbH

Business Line Silica HPC 911-221 A Rodenbacher Chaussee 4 63403 Hanau-Wolfgang Germany PHONE +49 6181 59-3936 FAX +49 6181 59 4489 technical.service.aerosil@ evonik.com www.aerosil.com

North America Evonik Corporation

Business Line Silica

2 Turner Place
Piscataway, NJ 08855-0365
USA
PHONE +1 888 SILICAS
PHONE +1 732 981-5000
FAX +1 732 981-5275
technical.service.aerosil@
evonik.com
www.aerosil.com

Asia (excluding Japan) Evonik Specialty Chemicals (Shanghai) Co.,Ltd

Business Line Silica 55 Chundong Road Xinzhuang Industry Park Shanghai 201108 P.R. China PHONE +86 21 6119-1065 FAX +86 21 6119-1075 technical.service.aerosil@ evonik.com www.aerosil.com

Japan NIPPON AEROSIL CO., LTD.

Applied Technology Group 3 Mita-Cho Yokkaichi, Mie 510-0841 Japan PHONE +81 59 345-5270 FAX +81 59 346-4657 infonac@evonik.com www.aerosil.jp

