

Product Fact Sheet




POLYGLYKOL[®] D 21/700

Base oil component

COMPOSITION

random ethylene oxide/propylene oxide copolymer



n:m = 2:1

CAS-Nr.: 9003-11-6

CLARIANT INTERNATIONAL LTD

Rothausstrasse 61
4132 Muttenz
Switzerland

BUSINESS UNIT INDUSTRIAL &
CONSUMER SPECIALTIES

www.ics.clariant.com
www.clariant.com

PRODUCT PROPERTIES ^{*)}		<i>approx.</i>	
Appearance at 20 °C	Clear viscous liquid	Density (DIN 51757)	[g/cm ³] (20 °C) 1.065 – 1.085
Colour index [APHA] (EN 1557)	max. 100	Cloud point (1% w/w in water)	[°C] 71
Refractive index at 20°C (DIN 51432, Part 2)	1.460 – 1.464	Viscosity (DIN 51562)	[mm ² /s] (40 °C) 1025
Molecular weight	[g/mol] 5600	Viscosity (DIN 51562)	[mm ² /s] (100 °C) 180
Water content (DIN 51777)	[%] max. 0.3	Viscosity Index (ASTM D2270)	298
pH value (10% w/w in water) (DIN EN 1557)	5.0 – 7.0	Pour point (ISO 3016)	[°C] -35
Four ball test (DIN 51350/3 B 60 min. / 300 N)	[mm] 0,57	Flash point (DIN 51376)	[°C] 250
Seizure Load/Welding Load	[N] 1400/1700	Ignition temperature (DIN 51794)	[°C] 375
FZG Load stage (DIN 51354)	>12	Sodium/potassium content	[ppm] max. 10

^{*)} These characteristics are for guidance only and are not to be taken as product specifications. The tolerances are given in the product specification sheet. For further information on product properties, toxicological, ecological and safety data, please refer to the safety data sheet.

PRODUCT PROPERTIES

Polyglykol D 21/700 is a clear neutral viscous liquid at room temperature. Polyglykol D 21/700 is soluble in water and polar organic solvents like acetone or methanol at room temperature. Polyglykol D 21/700 is insoluble in pure hydrocarbons. Polyglykol D 21/700 displays a very low solidification point of –35°C and no evaporation loss even at temperatures as high as 100°C. The hygroscopy of Polyglykols increase with the EO ratio in the polymer.

STORAGE

When stored in a cold, dry place in a closed container Polyglykol D 21/700 can be kept for at least two years.

APPLICATION

Based on their physical and chemical characteristics D 21-type polyglycols are used for a wide variety of applications.

Fields of industrial application:

- Base oil component for high performance lubricants with low friction coefficients, excellent wear properties and good thermal stability
- Lubricant for high pressure compressors
- Water soluble, lubricating component of metalworking fluids
- Component of auxiliaries for leather and textile processing
- Defoamer for food and non-food applications
- Reactive alcohol component in chemical reactions
- Solvent and humectants for dyes and inks
- Heat transfer medium

To increase the stability against thermo oxidative degradation, Lubricant Additive 1655 N can be used.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application. * Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

For sales to customers located within the United States and Canada the following applies in addition:
NO EXPRESS OR IMPLIED WARRANTY IS MADE OF THE MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE OF ANY PRODUCT OR SERVICE.

© Trademark of Clariant registered in many countries
© 2012 Clariant International Ltd



CLARIANT INTERNATIONAL LTD