

## **Evonik Corporation Rohacell® P 190 Polymethacrylimide (PMI) Rigid Foam Sheet (discontinued \*\*)**

Category: Other Engineering Material, Composite Core Material, Polymer, Thermoset, Polymethacrylimide

## **Material Notes:**

ROHACELL P 190 is a compacted grade with an oriented cell structure leading to high strength and rigidity in the plane of the sheet. General ROHACELL Information: ROHACELL is a closed-cell rigid expanded plastic material for lightweight sandwich construction. It has excellent mechanical properties, high dimensional stability under heat, solvent resistance and, particularly at low temperature, a low thermal conductivity. The strength and moduli values are the highest are the highest for any foamed plastic in its density range. ROHACELL is manufactured by hot forming of methacrylic acid/methacrylonitrile copolymer sheets. During foaming this copolymer is converted to polymethacrylimide. Information supplied by Emkay Plastics, Ltd.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Evonik-Corporation-Rohacell-P-190-Polymethacrylimide-PMI-Rigid-Foam-Sheet-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.191 g/cc	0.00689 lb/in³	ASTM D1622-63

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	8.34 MPa	1210 psi	ASTM D638-68
Elongation at Break	6.0 %	6.0 %	ASTM D638-68
Modulus of Elasticity	0.372 GPa	54.0 ksi	ASTM D638-68
Flexural Yield Strength	11.8 MPa	1710 psi	Perpendicular to Sheet; ASTM D 790- 66
	12.3 MPa	1780 psi	ASTM D790-66
Compressive Yield Strength	3.14 MPa	455 psi	Perpendicular to Sheet; ASTM D 1621-64
	7.65 MPa	1110 psi	ASTM D1621-64
Shear Modulus	0.0979 GPa	14.2 ksi	ASTM C273-61
Shear Strength	2.94 MPa	427 psi	Perpendicular to Sheet; ASTM C 273-61
	5.39 MPa	782 psi	ASTM C273-61

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	130 °C	266 °F	Dimensional stability per DIN 53424; oriented cell structure starts to decrease beyond this temperature.



Descriptive Properties	Value	Comments
Color	White	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China