

# Dynasylan® DAMO-T

## N-(2-Aminoethyl)-3-aminopropyltrimethoxysilane

### Technical data

Properties and test methods	Value	Unit	Method
Refractive index n (20,D)	approx. 1.444	-	DIN 51423
Flash point	approx. 90/194	°C/ °F	DIN 51423
Viscosity (25 °C/ 68 ° F)	approx. 7/6.8	mPa's / cSt	DIN 53015
Density (20 °C/ 68 ° F)	approx. 1.03	g/cm <sup>3</sup>	DIN 51757

### Registrations

#### Dynasylan® DAMO-T

EINECS/ELINCS (EU):	Yes
AICS (Australia):	Yes
DSL/NDSL (Canada):	Yes
PICCS (Philippines):	Yes
TSCA (USA):	Yes
IECS (P.R. China):	Yes
ENCS (Japan):	Yes
ECL (South Korea):	Yes

**Dynasylan®** DAMO-T is a bifunctional organosilane possessing two reactive amino groups and hydrolyzable inorganic methoxysilyl groups.

The dual nature of its reactivity allows **Dynasylan®** DAMO-T to bind chemically to both inorganic materials (e.g. glass, metals, fillers) and organic polymers (e.g. thermosets, thermoplastics, elastomers), thus functioning as an adhesion promoter and surface modifier.

**Dynasylan®** DAMO-T is a yellow liquid with an amine-like odor. It is soluble in alcohols, and aliphatic or aromatic hydrocarbons.

### Safety and handling

Before considering the use of Dynasylan® and Protectosil® products please read its Material Safety Data sheet (MSDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Material Safety Data Sheet is available after registration on our website [www.dynasylan.com](http://www.dynasylan.com) or upon request from your local representative, customer service or from Evonik Industries AG, Product Safety Department, E-MAIL [sds-im@evonik.com](mailto:sds-im@evonik.com).

### Packaging and storage

**Dynasylan®** DAMO-T is supplied in 25 kg and 200 kg drums and 950 kg containers. In the unopened container **Dynasylan®** DAMO-T has a shelf life of at least one year.

## Properties and application

**Dynasylan**<sup>®</sup> DAMO-T is an important additive in applications such as:

- glass fibre/glass fabric composites: as a finish or size constituent
- glass and metal primers
- foundry resins: as an additive to various types of foundry resins
- sealants and adhesives: as a primer or additive
- mineral-filled polymers (composites): for pretreatment of fillers and pigments or as an additive
- paints and coatings: as an additive and/or primer for improving adhesion to the substrate.

The most important effects which can be achieved through the use of **Dynasylan**<sup>®</sup> DAMO-T are:

improved product properties, such as

- flexural strength, tensile strength, impact strength and modulus of elasticity
- moisture and corrosion resistance

improved in processing properties, such as

- adhesion

## Reactivity

In the presence of water the methoxy groups of **Dynasylan**<sup>®</sup> DAMO-T hydrolyze to form reactive silanol groups which can bond to a variety of inorganic substrates. The organophilic diamino group of **Dynasylan**<sup>®</sup> DAMO-T can react with a suitable polymer.

The hydrolysis of **Dynasylan**<sup>®</sup> DAMO-T takes place autocatalytically. The pH value of the hydrolysate is about 10-11. For a longer stability of the hydrolysate a pH of 4 is recommended. Examples of suitable inorganic substrates are glass or glass fibers.

**Dynasylan**<sup>®</sup> DAMO-T may be used with such polymers as phenolic, furan resins, PA, PBT, PC, EVA, modified PP, PVAC, PVC, acrylates and silicones.

**Dynasylan**<sup>®</sup> DAMO-T can undergo reactions with ketone or ester solvents. The silane or silanized substrates can react with carbon dioxide to form the corresponding carbonates and/or carbamates.

## Processing

For substrate pretreatments (e.g. as a primer) **Dynasylan**<sup>®</sup> DAMO-T may be used as an approximately 0.5-2 wt.-% solution in an organic solvent such as alcohol, as a constituent of aqueous sizes or solutions, neat, or added to the polymer as an additive (at higher concentration: 1-10 wt.-%).

This information and all technical and other advice are based on Evonik's present knowledge and experience. However, Evonik assumes no liability for such information or advice, including the extent to which such information or advice may relate to third party intellectual property rights. Evonik reserves the right to make any changes to information or advice at any time, without prior or subsequent notice. EVONIK DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, AND SHALL HAVE NO LIABILITY FOR, MERCHANTABILITY OF THE PRODUCT OR ITS FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE), OR OTHERWISE. EVONIK SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. It is the customer's sole responsibility to arrange for inspection and testing of all products by qualified experts. Reference to trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used.

#### **Europe/Middle-East/Africa/RoW**

##### **Evonik Industries AG**

Inorganic Materials  
Rodenbacher Chaussee 4  
63457 Hanau-Wolfgang  
Germany  
PHONE +49 6181 59 13636  
FAX +49 6181 59 13737  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Degussa (SEA) Pte. Ltd.**

Inorganic Materials  
3 Internatioanl Business Park  
#07-18, Nordic European Centre  
Singapore 609927  
PHONE +65 6809 6830  
FAX +65 6809 6630  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Taiwan Ltd.**

Inorganic Materials  
Artist Construction Bldg.  
9F, No. 133  
Min Sheng East Road, Sec 3  
Taipei, 105 Taiwan, R.O.C.  
Taiwan  
PHONE +886 227 17 1242  
FAX +886 227 17 2106  
dynasytan@evonik.com  
www.dynasytan.com

#### **North America**

##### **Evonik Degussa Corporation**

Inorganic Materials  
P.O. Box 677  
299 Jefferson Road  
Parsippany, NJ 07054-0677  
USA  
PHONE (TOLL FREE) +1 800 237 67 45  
PHONE +1 973 929 8513  
FAX +1 973 929 8503  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Degussa (Shanghai) Co. Ltd.**

Inorganic Materials  
55, Chungdong Road  
Shanghai 201108  
P.R. China  
PHONE +86 21 6119 1053  
FAX +86 21 6119 1075  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Japan Co. Ltd**

Inorganic Materials  
12th Floor Monolith Building  
2-3-1, Nishi-Shinjuku-ku  
Tokyo 163-0912  
Japan  
PHONE +81 353 23 7300  
FAX +81 353 23 7399  
dynasytan@evonik.com  
www.dynasytan.com

#### **Latin America**

##### **Evonik Brasil Ltda.**

Inorganic Materials  
Alameda Campinas, 579  
01404-000 São Paulo-SP  
Brazil  
PHONE +55 11 3146 4123  
FAX +55 11 3146 4109  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Korea Ltd.**

Inorganic Materials  
94, Galsan 1-dong  
Bupyeong-gu  
Incheon, 403-081  
Korea  
PHONE +82 32 510 2433  
FAX +82 32 505 2510  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik India Pvt. Ltd.**

Inorganic Materials  
Krislon House  
Saki Vihar Road, Anderi (E)  
Mumbai - 400 072  
India  
PHONE +91 226 7238 800  
FAX +91 226 7238 811  
dynasytan@evonik.com  
www.dynasytan.com