

Construction Polymers

Technical Data Sheet

Melflux[®] 2651 F



Chemical Nature

Melflux[®] 2651 F is a free-flowing spray dried powder of a modified polycarboxylic ether. High performance superplasticizer for cement based construction materials.

Properties

Typical Properties

Physical shape	powder
Appearance	characteristic, yellowish to brownish
Drying loss	max. 2.0%
Bulk density	300 – 600 kg/m ³
Dosage recommendation	0.05 – 1.00%
by weight of cementitious material	
pH value at 20 °C, 20% solution	6.5 – 8.5

Applications

Fields of application

Melflux[®] 2651 F is optimized for plastification and water reduction of cementitious construction materials provides an excellent development of early strength; including the following:

- Self-leveling underlayments (SLU)
- Feather edge products
- Cementitious fast-setting floor screeds
- Cementitious self-leveling floor screeds
- Injection mortars
- Repair mortars
- Non-shrink grouts
- Cementitious floor screeds
- Tile adhesives and joint fillers
- Dry mix concrete

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Material Safety Data Sheet

All safety information is provided in the Material Safety Data Sheet for Melflux[®] 2651 F.

Transport Regulation

Not known as a dangerous good according to transport regulations.

Storage

Melflux® 2651 F has a shelf life of 1 year. It is to be stored in its unopened original packaging, dry and cool (not exceeding 40°C / 104°F). Do not double stack pallets, product may cake when exposed to pressure and friction.

Packaging

15 kg / 33 lb paper bags

Additional Notes

Melflux® 2651 F is a superplasticizer based on latest polymer technology. These types of superplasticizers typically contain certain side chains based on polyethylene glycol. Due to raw material synthesis of the polyethylene glycol, the nature of radical polymerization and the composition, it is known that this technical product has some natural color variations from nearly colorless to yellowish up to slightly brownish. However, these color variations have no influence on the application performance of the product. It is not known that the product colour changes significantly over time under normal storage conditions.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Melflux is a registered trademark of BASF Group.

© BASF Corporation, 2011



Responsible Care®
Good Chemistry at Work

BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® goto:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico



U.S. & Canada

BASF Corporation
Dispersions and Pigments
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions

Europe

BASF Construction Polymers GmbH
Dr.-Albert-Frank-Straße 32, 83308
Trostberg / Germany
Phone: +49 8621 86-16
Fax: +49 8621 86-29 95
Email: construction-polymers@basf.com
www.construction-polymers.com