

# TEGO® Antifoam 2–89

TEGO® Antifoam 2–89 is an antifoam emulsion based on organo–modified siloxanes.

## Physical properties

Appearance	white emulsion
Active content	20 %
Density (25 °C)	approx. 1.0 g/cm <sup>3</sup>
Viscosity, dynamic (25 °C) DIN 53019	approx. 400 mPas
pH–value (25 °C)	8,5 delivered form

## Application

TEGO® Antifoam 2–89 provides reliable foam control and excellent long–term efficiency especially in pressure sensitive adhesives. It may also be used in aqueous media, as well as in the processing and application of polymer dispersions, emulsions and a multitude of other industrial applications (e.g. industrial and household cleaners) where the use of traditional silicone oil based antifoams is restricted for certain reasons.

## Benefits

The special raw material of TEGO® Antifoam 2–89 provide an unique product profile that combines excellent efficiency with maximum compatibility at the same time. These properties cannot be achieved with organic or with traditional silicone oil based antifoams.

Furthermore undesirable effects associated with silicone based antifoams (silicone spotting, fish eyes) can be eliminated in most applications.

The TEGO® Antifoam product range exceeds customer requirements according to:

- Foam formation during compounding of a final formulation
- Foam formation during the application of the adhesive
- Inadequate storage stability


## Dosage

In most applications it is beneficial to apply TEGO® Antifoam 2–89 pre–diluted in water (1 : 1 to 1 : 10).

Depending on the application in question the required dosage may vary over a wide range (0.05 – 0.2 %). Suitable screening tests are therefore recommended (initial dosage: 0.1 %).

## Handling

Dilution of TEGO® Antifoam 2–89 may be prepared by adding the desired amount of water to TEGO® Antifoam 2–89 while stirring gently at low shear rates.



The pre–dilution will shorten the storage stability. 1 : 1 dilutions prepared as described above are stable for several days. 1 : 10 dilutions should be processed within several hours.

The product has to be stirred before use.

### Food contact status

#### FDA Regulation

TEGO® Antifoam 2–89 complies with 21 CFR 176.210 (Defoaming agents used in the manufacture of paper and paperboard) and 21 CFR 175.105 (Adhesives).

#### European Regulation 10/2011 and amendments

Detailed information is available on request.

#### BfR Recommendations

TEGO® Antifoam 2–89 complies with the XIVth BfR Recommendation.

Polymer dispersions that comply with the XIVth Recommendation may be further used as production auxiliary according to the BfR Recommendation XXXVI under B. I. 10.

#### Registration status

The components of TEGO® Antifoam 2–89 are listed in the following chemical inventories:

EINECS, TSCA, DSL, ENCS, AICS, ECL, PICCS, CHINA and Taiwan

### Storage stability

TEGO® Antifoam 2–89 is stable in closed containers for a minimum of 6 months.

TEGO® Antifoam 2–89 must be stored in frost-free conditions.

#### Packaging

210 kg plastic drums (840 kg each pallet)  
1 000 kg containers

#### Hazardous goods classification

Information concerning

- classification and labelling according to regulations for transport and for dangerous substances
- protective measures for storage and handling
- measures in case of accidents and fire
- toxicity and ecological effects

is given in our material safety data sheets.

07/2015

#### Trademark notice and legal notice

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

(Status: July 2015)

#### Evonik Nutrition & Care GmbH

Goldschmidtstr. 100, 45127 Essen, Germany

Phone Europe +49 201 173–2665, Asia +86 21 61191 125, Americas +1 804 727 0700

interface-performance@evonik.com, www.evonik.com/interface-performance