

TEGO® Surten W 111

TEGO® Surten W 111 is a non-ionic organic surfactant.

Physical properties

| | |
|-------------------|--------------------------------|
| Appearance | colorless, clear liquid |
| Active content | 100 % |
| Density (25 °C) | approx. 0.95 g/cm ³ |
| Viscosity (25 °C) | low viscous |

Application

- TEGO® Surten W 111 improves the wetting properties of aqueous dispersions on difficult substrates and may therefore be used in a variety of applications of pressure sensitive adhesives in high dynamic processes.
- Formulation and application of polymer dispersions/latices with fillers or pigments, e. g. paper coatings
- Improves the wetting and spreading properties of aqueous media such as full synthetic and semi synthetic Metal Working Fluids (MWF). Additionally it provides excellent dispersing properties on finely ground aluminium swarf
- In a multitude of other industrial applications where negative interaction between substrates and coatings has to be overcome

Benefits

TEGO® Surten W 111 is a very low foaming wetting agent for water based systems. It is solvent and silicone-free.

Due to the special selection of active ingredients TEGO® Surten W 111 outperforms conventional wetting agents due to the low foaming behavior and its fast surface migration.

Dosage/Handling

TEGO® Surten W 111 may be added to the dispersion as delivered.

Pre-dilutions are possible and could be beneficial depending on the facilities.

Depending on the application in question the required dosage may vary over a wide range (0.1 % to 1.0 %); suitable screening tests are therefore recommended (initial dosage 0.3 %).

Food contact status

Information on the food contact status of TEGO® Surten W 111 is available on request.

Registration status

The components of TEGO® Surten W 111 are listed in the following chemical inventories:

EINECS, TSCA (restricted to the a.m. application fields), DSL, ECL, ENCS, PICCS, IECSC and AICS

Storage stability

TEGO® Surten W 111 is stable in closed containers for a minimum of 12 months.

Packaging

190 kg steel drum (760 kg each pallet)

Hazardous goods classification

Information concerning

- classification and labelling according to regulations for transport and for dangerous substances
- protective measures for storage and handling
- measures in case of accidents and fire
- toxicity and ecological effects

is given in our material safety data sheets.

09/2013

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

(Status: April 2008)

Evonik Industries AG

Goldschmidtstraße 100, 45127 Essen, Germany

Phone Europe +49 201 173-2175, Asia +86 21 61191 125, Americas +1 804 541 8658

Interface-performance@evonik.com, www.evonik.com/interface-performance