

# PLASTISTRENGTH®

## ACRYLIC PROCESS AID

Product Data Sheet

## PLASTISTRENGTH 550

Good dispersion in rigid PVC for better transparency and uniformity of compounds in film / sheet and bottle applications .

### PHYSICAL PROPERTIES

Characteristics	Methods	Specifications
Aspect		White powder
Solution viscosity	PH-30	0. 25 to 0. 35
Bulk density	GR-23	0.40 to 0.60 g / cm3
Foreign matter	PH-37	Equal to standard
Particle size 425 Mesh	GR-24	< 2%
Percent volatiles	GR-21	< 1. 2 %
Heat stability	PH-25	Equal to standard

### PACKAGING

20 kg bags ( 1000 kg per pallet)  
500 kg bags ( 1000 kg per pallet)

### PRODUCTION & STORAGE

Vlissingen (Holland) . ISO 9000.V2000 certified – ISO 14.000 certified  
Mobile (USA) ISO 9000:V2000

### HEALTH & SAFETY

Consult the MSDS of P550

ARKEMA France société anonyme au capital de 68.685.704 Euros – R.C.S Nanterre B 319 632 790  
Siège social : 420 rue d'Estienne d'Orves – F – 92700 Colombes – Hauts de seine (France)



Libdura/ProductDataSheetPlastistrength/Issue1/041004

---

The information contained in this document is based on trial carried out by our Research Centres and data selected from the literature, but shall in no event be held to constitute or imply any warranty, undertaking ,express or implied commitment from our part. Our formal specifications define the limit of our commitment. No liability whatsoever can be accepted by ARKEMA with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.

