

GALSTAFF MULTIRESINE

SPECIALITY RESINS AND AUXILIARIES

SYNTEVEN 709-1

Product description

SYNTEVEN 709-1 is direct gloss unsaturated polyester in Butyl Acetate, highly reactive and high glossy.

Main Applications

SYNTEVEN 709-1 is used in the formulation for wood and furniture ,clear or pigmented ,conventional curing with high reactivity.

Properties

SYNTEVEN 709-1 permits the formulation of wood coatings and the films cured by conventional methods result very hard with excellent flow and easy to sand.

Specifications

<u>Properties</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Viscosity at 25 °C	2500 – 2800	mPa.s	GA 005.1
Non-volatile content	79 – 81	%	GA 006.1
Colour Hazen (Apha)	max 150		GA 003.1
Acid value	15 - 25	mgKOH/g	GA 004.2

Additional properties*

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Stability at 25 °C	6	months	

* These values provide general information and are not part of the product specification.

Storage

The resin should be stored indoors, in the original packaging, at temperatures between 5°C and 30°C .Exposure to direct sunlight should be avoided. The properties of the product might change during storage.

Safety

Please consult the Safety data sheet before working with this product.

The information contained in this data sheet is based on laboratory data and field experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any liability for occurrences arising out of its use. The user, by accepting the products described herein, agrees to be responsible for thoroughly testing each such product before committing to production. Our recommendations should not be taken as inducements to infringe any patent or violate any law, safety code or insurance regulation.

Ed: 27/04/2012 Ver 03 Pag. 1/1

