

GALSTAFF MULTIRESINE

SPECIALITY RESINS AND AUXILIARIES

SYNTEVEN 105

Product description

SYNTEVEN 105 is a monomer free unsaturated polyester resin, low viscose.

Application

SYNTEVEN 105 is suitable as binder in the manufacturing of pigment pastes.

Specification

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Acid value	18 – 22	mg KOH/g	GA 004.1
Viscosity at 23°C	600 – 700	mPa·s	GA 005.1

Additional properties*

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Density at 20°C	appr. 1,15	g/ml	DIN 53217/2
Stability at 25°C	12	months	

* These values provide general information and are not part of the product specification.

Storage

The resin should be stored indoors, in the original packaging, at temperatures between 5°C and 30°C .Exposure to direct sunlight should be avoided. The properties of the product might change during storage.

Safety

Please consult the Safety data sheet before working with this product.

The information contained in this data sheet is based on laboratory data and field experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any liability for occurrences arising out of its use. The user, by accepting the products described herein, agrees to be responsible for thoroughly testing each such product before committing to production. Our recommendations should not be taken as inducements to infringe any patent or violate any law, safety code or insurance regulation.

Ed: 18/04/2013 Ver 05 Pag. 1/1

