

# GALSTAFF MULTIRESINE

SPECIALITY RESINS AND AUXILIARIES

## SYNTEVEN 725

### Product description

**SYNTEVEN 725** is a reactive and slightly flexible unsaturated polyester resin.

### Application

**SYNTEVEN 725** is used to formulate clear and pigmented wood coatings ,containing wax-paraffin for conventional (Cobalt/Peroxide system) or U.V. curing.

### Properties

**SYNTEVEN 725** is used to formulate clear and pigmented coatings with high hardness and good flow properties.

### Specification

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Viscosity 25°C	1.400 – 1.600	mPas	GA 005.13
Non-volatile content	67 – 69	%	GA 006.1
Hazen colour(Apha)	max 150		GA 003.1
Acid value	max 30	mg/KOH/g	GA 004.1

### Additional properties\*

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	<u>Norm/Method</u>
Stability at 25°C	6	months	

\* These values provide general information and are not part of the product specification.

### Storage

The resin should be stored indoors, in the original packaging, at temperatures between 5°C and 30°C .Ex posure to direct sunlight should be avoided. The properties of the product might change during storage.

### Safety

Please consult the Safety data sheet before working with this product.

The information contained in this data sheet is based on laboratory data and field experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any liability for occurrences arising out of its use. The user, by accepting the products described herein, agrees to be responsible for thoroughly testing each such product before committing to production. Our recommendations should not be taken as inducements to infringe any patent or violate any law, safety code or insurance regulation.

Ed:8/09/2015 Ver 03 Pag. 1/1

