GALSTAFF MULTIRESINE

SPECIALITY RESINS AND AUXILIARIES

SYNTEVEN 9075 XA

Product description

SYNTEVEN 9075XA is fatty acids modified saturated polyester approx. 75% in Xylene/ButylAcetate (90/10).

Application

SYNTEVEN 9075XA is used to formulate two pack polyurethane coatings for wood or metal support. It also suitable to formulate tinting pastes and in combination with amino resins stoving enamels.

Properties

SYNTEVEN 9075XA is well suited for use in the formulation of two pack polyurethane systems in combination with aliphatic isocynate for high yellowing resistances.

Specification

<u>Property</u> Colour Hazen(Apha) Acid value	<u>Range</u> max 150 max 12,0	<u>Unit of measure</u> mg KOH/g	<u>Norm/Method</u> GA 003.1 GA 004.1
Viscosity 23°C	6000 – 10000	mPa₊s	GA 005.1
Non-volatile content	74 -76	%	GA 006.1
Water content	max 0,10	%	GA 009

Additional properties*

<u>Property</u>	<u>Range</u>	<u>Unit of measure</u>	Norm/Method
Density at 20℃	aprox. 1,15	g/ml	DIN 53217/2
Water content	max 0,10	%	GA 009
Stability at 25℃	12	months	
OH content	3.3 – 4.1	%	

* These values provide general information and are not part of the product specification.

Storage

The resin should be stored indoors, in the original packaging, at temperatures between 5°C and 30°C. E xposure to direct sunlight should be avoided. The properties of the product might change during storage.

Safety

Please consult the Safety data sheet before working with this product.

The information contained in this data sheet is based on laboratory data and field experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any liability for occurrences arising out of its use. The user, by accepting the products described herein, agrees to be responsible for thoroughly testing each such product before committing to production. Our recommendations should not be taken as inducements to infringe any patent or violate any law, safety code or insurance regulation.

Ed: 02/01/2012 Ver 04 Pag. 1/1





GALSTAFF MULTIRESINE S.p.A - Via Stazione, 90 - 21020 Mornago (ITALY) Tel.: +39-0331-9014.1 Fax: +39-0331-903777 mail sales@galstaffmultiresine.com Capitale sociale 5.000.000,00 € i.v. – R.E.A. 140430 - R.I. MI / C.F. 02268920960 P.Iva IT-10798700158 Sede legale / Registered Office: Via S. Senatore, 8 - 20122 Milano (ITALY) Stabilimenti / Production sites: Agrate Brianza (MI) – Mornago (VA) – Garbagnate Milanese (MI)