

Foamaster[®] WO 2323

(old: Foamaster[®] 223)



The Chemical Company

general	defoamer for low-odor emulsion paints
chemical nature	formulation based on white oil and non-ionic surfactants

Properties

physical form	opaque whitish liquid								
shelf life	When stored under the usual appropriate storage conditions, the product can be stored for 1 year.								
typical properties (no supply specification)	<table><tr><td>density at 20 °C (68 °F)</td><td>~ 0.88 g/cm³</td></tr><tr><td>water content</td><td>~ 0.025%</td></tr><tr><td>dilution appearance at 25 °C (77 °F)</td><td>~ 2.5%</td></tr><tr><td>Brookfield viscosity at 23 °C (73 °F)</td><td>~ 1,250 mPa · s</td></tr></table>	density at 20 °C (68 °F)	~ 0.88 g/cm ³	water content	~ 0.025%	dilution appearance at 25 °C (77 °F)	~ 2.5%	Brookfield viscosity at 23 °C (73 °F)	~ 1,250 mPa · s
density at 20 °C (68 °F)	~ 0.88 g/cm ³								
water content	~ 0.025%								
dilution appearance at 25 °C (77 °F)	~ 2.5%								
Brookfield viscosity at 23 °C (73 °F)	~ 1,250 mPa · s								

Application

	Foamaster [®] WO 2323 is a defoamer for manufacturing and application of emulsion paints.
recommended concentrations	0.1 – 0.3%, calculated on the paint

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted

BASF SE
Formulation Additives
67056 Ludwigshafen, Germany
www.dispersions-pigments.basf.com
formulation-additives-asia@basf.com
formulation-additives-europe@basf.com
formulation-additives-nafta@basf.com
formulation-additives-south-america@basf.com