



TECHNICAL DATA SHEET

ADK STAB

RX-267T EX

Description:

ADK STAB RX-267T EX, One package type Ca/Zn powder stabilizer. There is no heavy metal (Cd-free, Pb-free, Ba-free) and available in mixed metal powder form. It matches to lead stabilizer in heat stability, color stability and processibility.

Temporary

Typical Physical Properties:

Appearance	Pale blue powder
Contamination	No containing contamination
Bulk Specific Gravity	0.30-0.60
Performance test	NO difference to standard sample
Packing:	Net 20 KG, Bag.

Testing Method:

Appearance	Visual Inspection
Contamination	Visual Inspection
Bulk Specific Gravity	(JIS K 6721)
Performance test	Heat Stability

Application & Recommendation:

ADK STAB RX-267T EX is effective for rigid PVC profile, used in powder compounds. It's recommended at 3.0 phr – 5.0 phr. It's used with external & internal lubricant.

The information contained herein is based on our present state of knowledge and is intended to provide general notes on our products and their uses. Any recommendations or suggestion which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained in this publication shall be construed as a recommendation for any use that may infringe patent rights. Readers are cautioned to satisfy themselves as to the suitability of such goods for to purposes intended prior to use.