

# WACKER® POLYMER FD 6

## **Product description**

CAS No.: 70131-67-8

Colorless, clear, odorless liquid, not miscible with water.

#### **Special features**

α,ω- Dihydroxypolydimethylsiloxane

## **Application**

WACKER® POLYMER FD 6 is used as a raw material for the production of RTV-1-silicone rubbers.

#### **Storage**

The 'Best use before end' date of each batch is shown on the product label.

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

## Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site http://www.wacker.com.

Product data		
Typical general characteristics	Inspection Method	Value
Density at 20 °C	DIN 51757	approx. 0,98 g/cm3
Viscosity, dynamic at 23 °C	-	approx. 6000 mPa.s
Refractive index at 25 °C	DIN 51423	1,404
Ignition temperature (liquids)	DIN 51794	approx. 430 °C

These figures are only intended as a guide and should not be used in preparing specifications.

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

The management system has been certified according to DIN EN ISO 9001 and DIN EN ISO 14001

WACKER® is a trademark of Wacker Chemie AG.

For technical, quality, or product safety questions, please contact:

Wacker Chemie AG Hanns-Seidel-Platz 4 81737 München, Germany info.silicones@wacker.com

www.wacker.com