

MA 1209

SOLVENT BASED RELEASE AGENT FOR MOLDED POLYURETHANES

PRODUCT DESCRIPTION

MA 1209 is a production proven release coating for molded polyurethane parts. It provides fast and easy removal of molded Polyurethane foam. The product is most suitable for use with rigid and flexible Polyurethane molded Foam products.

TYPICAL PRODUCT DATA

Color & Appearance	White
Dispersing Medium	Heptane/Naphtha
Specific Gravity	0. 680- 0.730

KEY PERFORMANCE PROPERTIES

- Easy to apply.
- Fast air cure.
- Easy removal of the molded parts.
- Clean, dry, colourless and transparent coating.
- No flow marks or dent patches on the product surface
- Frictionless coating to increase the flow property of the polymer
- Leads to increased productivity and reduced scrap rate.
- Economical compared to other available products

USES

Recommended for flexible moulded Polyurethane Seats.

METHOD OF APPLICATION

MA 1209 is available in ready to use form and no dilution is recommended. Before application of MA 1209 on the mold surface ensure that all previously used release coatings are removed to provide clean, dry mold surface. Spray a thin, even film over the entire mold surface to be coated and allow drying. Best result is obtained with 0.5mm gun and 120gm/min discharge.



SAFETY AND HANDLING

The Material Safety Data Sheet on MA 1209, which accompanies initial shipment, should be reviewed prior to using the product.

Freezing of the product should be avoided.

AVAILABILITY

MA 1209 is supplied in 5 litre and 20 litre containers.

The information herein is believed to be reliable, but it is the user's responsibility to determine suitability of use; since we cannot know conditions of use, we make no warranties and assume no liability concerning use of the information. Nothing herein should be taken as an inducement to infringe any patent.