

## MA 2028

### RELEASE AGENT FOR POLYURETHANES

#### PRODUCT DESCRIPTION

MA 2028 is a production proven release coating for molded polyurethane parts. It provides fast and easy removal of molded Polyurethane parts. The product is suitable for use with Cast Urethane, Rigid Foams, and Integral Skin products.

#### TYPICAL PRODUCT DATA

Color & Appearance	Slightly White
Solids	100%
Specific Gravity	0.95

#### KEY PERFORMANCE PROPERTIES

- Easy to apply
- Minimal migration
- Improved part appearance
- Reduced rejection
- Non-staining
- No build-up

#### USES

Recommended for: Polyurethane Parts, Urethane Foam, Close Cell, Integral Skins, Urethane Elastomers, and Epoxy.

#### METHOD OF APPLICATION

MA 2028 is a concentrate and needs dilution with recommended solvents- Toluene, Hexane, or Heptane. One part material can be diluted with 15 to 30 parts of solvent. Before application of MA 2028 on the mold surface ensure that all previously used release coatings are removed to provide a clean, dry mold surface. Spray a thin, even film over the entire mold surface to be coated and allow to dry. Re-apply as required. No baking necessary.

## **SAFETY AND HANDLING**

The Material Safety Data Sheet on MA 2028, which accompanies initial shipment, should be reviewed prior to using the product.

Freezing of the product should be avoided.

## **AVAILABILITY**

MA 2028 is supplied in 5litre and 20 litre containers.

The information herein is believed to be reliable, but it the user's responsibility to determine suitability of use; since we cannot know conditions of use, we make no warranties and assume no liability concerning use of the information. Nothing herein should be taken as an inducement to infringe any patent.