

**Technical Data Sheet**  
**Long Oil Alkyd Resin**  
**ALT505 - W70**



**Characteristics:**

<b>Type of fatty acid</b>	<b>Soya</b>
<b>Solid Content (%)</b>	<b>70±1</b>
<b>Type of Solvent</b>	<b>White Spirit</b>
<b>Viscosity (25° C/Gardner)</b>	<b>1500 – 4000 (Sec)</b>
<b>Color (Gardner)</b>	<b>8 Max</b>
<b>Acid Value (mgKOH/g)</b>	<b>12 Max</b>

**Features:**

- Very high viscosity
- Very good adhesion

**Applications:**

- Metal structural coatings
- Anti-corrosion and Anti rust primers
- Industrial primers
- Wood and metal primers

**Shelf Life:**

This product must be stored in its original sealed steel drum in a cold and dry place away from fire, heat source and direct sunlight in temperatures between 5-30°C. Under these conditions, the shelf life of this product will be maximum 12 months from delivery time

**Packaging:**

190 Kg net in steel drum

**Remark:**

Solid content, Viscosity and other Qualitative parameters, are customizable based on customer requirements

**Email:** Info@t-sf.info

**Address:** Unit 1105, No. 2, Shahab tower, Ramatia Alley, Valiasr Street, Tehran, Iran

**Phone:** (+98) 21-88714573

**Fax:** (+98) 21-88553720

**GSM.:** (+98) 912-7125145