

**Technical Data Sheet**  
**Medium Oil Alkyd Resin**  
**AMT603 - W60**



**Characteristics:**

<b>Type of fatty acid</b>	<b>Special</b>
<b>Solid Content (%)</b>	<b>60±1</b>
<b>Type of Solvent</b>	<b>Mix of White Spirit &amp; Xylene</b>
<b>Viscosity (25° C/Gardner)</b>	<b>400 – 800 (Sec)</b>
<b>Color (Gardner)</b>	<b>2 Max</b>
<b>Acid Value (mgKOH/g)</b>	<b>10 Max</b>

**Features:**

- Excellent hardness
- Excellent surface and deep drying
- Excellent gloss and gloss retention
- Very good adhesion and flexibility
- Very good pigment wetting and dispersing
- Very good solvent acceptance

**Applications:**

- Auto body repair paints
- Industrial machinery coatings
- Cabinet and spray paints
- Industrial air-drying paints

**Shelf Life:**

This product must be stored in its original sealed steel drum in a cold and dry place away from fire, heat source and direct sunlight in temperatures between 5-30°C. Under these conditions, the shelf life of this product will be maximum 12 months from delivery time

**Packaging:**

190 Kg net in steel drum

**Remark:**

Solid content, Viscosity and other Qualitative parameters, are customizable based on customer requirements