

Technical Data Sheet

Short Oil Alkyd Resin

AST704 - X60



Characteristics:

Type of fatty acid	Coconut
Solid Content (%)	60±1
Type of Solvent	Xylene
Viscosity (25 [°] C/Gardner)	50 – 80 (Sec)
Color (Gardner)	1 Max
Acid Value (mgKOH/g)	10 Max

Features:

- Very good hardness
- Excellent gloss and gloss retention
- Excellent adhesion and flexibility
- Excellent pigment wetting and dispersing
- Good solvent acceptance

Applications:

- Amino resin based stoving paints
- Alkyd amin varnishes
- Nitro-cellulose paints, lacquers and putties
- Acid curing coatings
- Printing ink paints curing with acids

Shelf Life:

This product must be stored in its original sealed steel drum in a cold and dry place away from fire, heat source and direct sunlight in temperatures between 5-30°C. Under these conditions, the shelf life of this product will be maximum 12 months from delivery time

Packaging:

200 Kg net in steel drum

Remark:

Solid content, Viscosity and other Qualitative parameters, are customizable based on customer requirements

Email: Info@t-sf.info

Address: Unit 1105, No. 2, Shahab tower, Ramatia Alley, Valiasr Street, Tehran, Iran

Phone: (+98) 21-88714573

Fax: (+98) 21-88553720

GSM.: (+98) 912-7125145