Product Fact Sheet SAPOGENAT® T 500

CLARIANT

Nonionic surfactant for the chemical industry

COMPOSITION

Tributylphenol ethoxylate with 50 moles ethylene oxide

PRODUCT PROPERTIES*)		
Active substance content	About 100 %	
Appearance at 20°C	yellowish wax	
Density (DIN 51757) at 70°C	about 1,05 g/cm ³	
Viscosity (DIN 53015) at 70°C	about 140 mPa*s	
Drop Point (DIN 51801)	about 54°C	
pH value (DIN EN 1262), 1% in water	6 - 8	
Flash point (DIN/ISO 2592)	about 250 °C	
Cloud point (1% in 100 ml 10% NaCl solution)	approx. 74°C	
HLB value	about 18	
Solubility at 20°C after 24 h	1% in water: 10% in mineral oil: 10% in xylene:	clear solution insoluble clear solution
BgVV Listing	BgVV Teil A XIV, XXXIV	

^{*)} These characteristics are for guidance only and are not to be taken as product specifications. The tolerances are given in the product specification sheet. For further information on product properties, toxicological, ecological and safety data, please refer to the safety data sheet.

USE

Sapogenat T 500 is used e.g. in the following applications:

- For pigment preparations
- for electroplating processes
- as emulsifier for waxes and solvents
- for polymer dispersions and emulsion polymerization.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application. 'Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

For sales to customers located within the United States and Canada the following applies in addition:

NO EXPRESS OR IMPLIED WARRANTY IS MADE OF THE MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE OF ANY PRODUCT OR SERVICE.

® Trademark of Clariant registered in many countries © 2012 Clariant International Ltd





CLARIANT INTERNATIONAL LTD

Rothausstrasse 61 4132 Muttenz Switzerland

BUSINESS UNIT INDUSTRIAL & CONSUMER SPECIALTIES

www.ics.clariant.com www.clariant.com

Page 1 of 1 SAPOGENAT T 500® Version 5.0 | June 2013